

**SMART WEATHER PROOF PA TELEPHONE** (WMHS-IIM) is a multiple role; multiple location operating telephone unit by construction with built in public address system, works as a normal telephone as well as a page phone unit. This phone has a built in amplifier, which is connected to external loudspeaker horn and works on either 220 volts AC or 110 Volts AC. One has to just lift the telephone handset of any extension, dial the extension number of PA Telephone and after the call matures automatically, make necessary announcement. The communication between the calling party and the called party is in private mode, when the called party lifts the handset.

**SMART WEATHER PROOF PA TELEPHONE** (WMHS-II M) disconnects automatically if the calling party disconnects the call. The announcement is made at specified location only and not all over the plant and at any time more than one person can make announcement on different PA telephone sets. Incoming call from the PA telephone is like normal telephone call, just lift the receiver and dial the required extension. It is essential for growing organisations because of its unique features and is proposed to be used in conjunction with **SMART MASTER CONTROL STATION** (MODEL MCS-II) OR WITH PLANT EPABX (The backbone of every establishments communication.)



## **OPERATIONS:**

#### 1. TO MAKE A CALL: -

- Lift the handset, hear the dial tone.
- Dial desired extension number & communicate.
- Replace handset to disconnect active call.

#### 2. INCOMING CALL: -

- From any phone dial the extension number of SMART PA TELEPHONE. It will connect automatically and acknowledge with a BEEP TONE.
- Announce after the hearing the BEEP TONE.
- Communication will be in PRIVATE MODE when called party lifts the receiver.
- Replacing the receiver on cradle will reset the SMART PA TELEPHONE.

#### VERSATILE APPLICATIONS

- **\*** Cement Plants. **\*** Mines. **\*** Petrochemical Refineries. **\*** Chemical Plants. **\*** Construction Sites.
- \* Steel Plants. \* Spinning Yarns \* Fertilizer Plants. \* Sugar Mills. \* Power Generation Facilities

 Pulp & Paper Mills # Food Processing Plant # Warehouses # Recreation Facilities #Hydroelectric Facilities # Drilling Rigs # Ammonia Storage Area # Process industries# ANY LARGE AND MEDIUM SCALE INDUSTRIAL UNITS.

## **ACCESSORIES AND OPTIONS**

- External Loudspeaker Horn.
- Color selection (subject to minimum quantities).

#### "(Specifications and description subjected to change without prior notice)"

#### **SMART CHOICE: -**

- Simple Installation.
- Simple Operation.
- One-piece waterproof non-tactile keypad.
- Magnetic reed hook-switch reduces moving parts subject to wear.
- AL alloy casting body with integrated canopy & Powder Coated surface finish.
- Heavy industrial ABS handset & SS cord.
- Noise-canceling type microphone.
- Auto disconnection to free line for next call.
- A service temperature range from 0 to +60 o C.
- Encapsulated circuit boards impervious to water and condensation.
- Environment Protected.
- Single PCB design for plug & play operation.
- Easy troubleshooting ensuring minimum downtime.

# SPECIFICATIONS: -

#### **Electrical Requirement:-**

<u>Lieenicai Requirement.</u>	
Power Source:	220 V AC / 110 V AC (SWITCH ABLE).
Phone line:	24 VOLTS (EPABX) / 50 VOLTS (TEL LINE).
Power consumption:	< 35 Watts.
Stand by consumption:	< 5 Watts.
Amplifier:	30 Watts (RMS).
Horn Speaker:	60 watts, 8 ohms.
Handset:	Standard hand set, four feet stainless steel Armour tube.
Insulation:	600 v for 3 min between power source & Telephone line.
Ringer Voltage:	75 V AC (150 V PP).
UPSLOAD	30VA (RMS) PEAK 50 VA.
Mechanical Specifications:-	

Dimensions: Net weight: Construction:

Cradle: Hand set construction: Standard mounting: Microphone:

#### Environmental:-

Moisture Resistance: Temperature Range: Dust resistance: 422 x 197 x 146 mm. 8 Kgs. AL alloy casting body with integrated canopy & Powder Coated surface finish. Al-Alloy with Magnetic reed switch. High impact ABS. Vertical wall / panel. Noise canceling dynamic.

0 to 95% humidity with PCB conformal coated. 0 to +60C. Fully weather proof enclosure.

# INDUSTRIAL COMMUNICATIONS SIMPLIFIED.

# Cables & Wireless Co.

FF 75 RAJAT ARCADE, MIDC T-POINT, AMRAWATI ROAD, WADI, NAGPUR -440023.MAHARASHTRA, INDIA.PHONE:-+917104-321913, +917104-224381 FAX: - +917104-224381. Cell: - +9198226 95746, +919225227945, +919822941190.Website: www.cnwcom.in, E-mail: - cnwcom@gmail.com