

SMART 4-20mA DISPLAY UNIT

MODEL-NSDU-44L

INTRODUCTION

SMART 4-20 mA is an safe wall mounting indicator which displays the current flowing in a 4/20mA process loop in meaningful engineering units. This is a versatile display unit which is used to measure a variety of process variables.

4" and 8" 7 segment LED displays are ideal for plant environments where process information is easily readable from very large distance, this also allows everyone in the plant to see information.

MAIN APPLICATION of the SMART 4-20 mA is to display a measured variable or control signal in a Industrial process area. The unit is factory calibrated to display any linear variable represented by a 4/20mA signal, such as temperature, pressure level, Vibration or actuator position.

MODEL:-

MODEL-NSDU-44L is Four digit SEVEN SEGMENT display of 4" showing DISPLAY readings from 0-9999.



MODEL-NSDU-83L is Three digit SEVEN SEGMENT display of 8" showing DISPLAY readings from 0-999.



SPECIFICATION :-

| | | |
|-----------------|----|--|
| POWER SUPPLY | :- | 90-250 VA |
| INPUT SIGNAL | :- | 4-20mA DC |
| DISPLAY UNIT | :- | 7 Segment LED Display Unit |
| ACCURACY | :- | +/- .25% of Full scale Or 1 count |
| FULL SCALE RANG | :- | MODEL-PD-4 '0-9999' & MODEL-PD-8 '0-999' |
| MOUNTING | :- | Weather Proof Wall mount design |
| DIMENSIONS | :- | MODEL NDU-4 - 180 x430 MM , MODEL NDU-8 – 330 X 630 MM |

ACCESSORIES :- External N/C Contact for Hooter/Flasher , CUSTOM SIZE ALSO AVAILABLE

INDUSTRIAL COMMUNICATIONS SIMPLIFIED .

cables & Wireless Co.

FF 75 RAJAT ARCADE, MIDC T-POINT,
AMRAWATI ROAD, WADI, NAGPUR -440023.

PHONE:-07104-321913,07104-224381.

Fax:- 07104-224381.

Cell: - 098226 95746, 09225227945, 09822941190.

Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.



"(Specifications and description subjected to change without prior notice)"