SMART

304 SS BAG COUNTER (MODEL BC-L-SS)

SMART BAG COUNTER in **304 GRADE STAINLESS STEEL** HOUSING DESIGNED SPECIALLY FOR CORROSIVE ATMOSPHERE.

This instrument is used for the exact counting of bags, it has a sensing head attachment in 304 SS grade stainless steel fitted on the spiral chute/conveyer or loader of the loading unit

The **SMART** BAG COUNTER is designed for display of number of bags loaded in the truck or wagon by respective loaders, with programmable counters to generate predefined signals after the counter figure is attained, non ohmic contact output is available for connecting external control devices.



The instrument is MICROCONTROLLER based, SWITCH MODE POWER SUPPLY UNIT (SMPS), KEYPAD / SOFTWARE for programming & counter setting & resetting, seven segment display unit for displaying RUNNING COUNT/PRESET COUNT.

Use of HIGH DURABLE 304 GRADE STAINLESS STEEL SENSING HEAD gives longer life in corrosive industrial atmosphere (UREA / FERTILISER PLANTS).

The unit has 2 display:-

- a) SIX SEVEN SEGMENT display of 4" showing running COUNTER readings from 0-999999.
- b) Four SEVEN SEGMENT display of 1/2" showing SET/RESET counts while programming

Both the displays are visible from long distance, when the reading reaches or exceeds the predefined count non-ohmic contact output is available for connecting external control devices like alarm, power down, count saving, computer interface, etc.

Features:

- Precise counting, high speed, durable & Intelligent to identify continuous bags
- Applicable for single bag counting, continuous bag counting and batch counting.
- Operating on 85-220 V AC SMPS based power supply unit.
- 304 SS Sensing head attachment
- Pre alarm (last 10 counts to go)
- External ACCESSORY relay contacts
- Power down count saving
- 6digit seven segment 6 x 4" count display.
- 4 digit seven segment 4 x 1" set / preset count display.
- Ethernet output for Computer connectivity with operating software; -windows based
- Wireless connectivity
- 304 GRADE STAINLESS STEEL HOUSING ,Weatherproof design for Corrosive atmospheres.
- Elegant in appearance, rugged & firm in construction.
- Alarm at predefined figure with belt tripping connection.

TECHNICAL SPECIFICATIONS

BAGGAGE COUNTER:

Electrical performance: -

Power Source 85 volts -240 V AC.

Power Supply SMPS .
Power consumption 3 Watts.
Count input mode Sensing Head

Working model accumulative counting (0-999999)

Display COUNTER(0-999999) SET/RESET(0-9999)

Output contact normally open and closed.

Environmental: -

Temperature 0 to +60 C.

Humidity 0 to 95% Rh non-condensing. Enclosure 304 grade SS .Dust proof type.

Mechanical: -

Body 304 Stainless Steel. Dimension 799X220X140

Net weight 8KG

Standard mounting WALL MOUNTING

INDUSTRIAL AUTOMATION SIMPLIFIED.

Cables & Wireless Co.

FF 75 RAJAT ARCADE, MIDC T-POINT,

AMRAWATI ROAD, WADI,

NAGPUR -440023.

PHONE:-07104-224381. Fax:- 07104-224381.

Website:- www.cnwcom.in. E-mail: - cnwcom@gmail.com.

Cell: - 098226 95746, 09822941190.

"(Specifications and description subjected to change without prior notice)"