

SMART HOOTER TELEPHONE LOUDRINGER

MODEL TR-III

SMART HOOTER can be connected with **SMART INDUSTRIAL TELEPHONES** or with TEL line of any EPABX system, it has an integrated annunciation system & can be connected directly to TEL line or in parallel with any TEL unit . Very useful in heavy, medium and small process industries.
When a call is made to the telephone, the **ACTIVATES** and the siren is heard over the loudspeaker of the hooter unit.



CONNECTIONS: -

- 1) Connect the hooter using single pair cable from the Industrial Telephone/ TEL LINE from EPABX SYSTEM/ in parallel with any make TEL UNIT.
- 2) Connect the power supply 220 VAC/ 110 VAC

TECHNICAL SPECIFICATIONS: -

ELECTRICAL PERFORMANCE: -

Audible range frequency response 300 – 3400 Hz.
Ringer output max 107 db @ 1 meter

ELECTRICAL REQUIREMENTS: -

Connection method PCB terminal block type.
Fuse 1 Amp 2AG fast blows.
Power supply 220 VAC / 110 VAC switch able.

ENVIRONMENTAL: -

Temperature 0 to +60 C.
Humidity 0 to 95% Rh non-condensing.
Enclosure Dustproof fully gasketed.

MECHANICAL: -

Body IP65 ABS.
Dimension of ABS BOX 140 x 120 x 100 mm.
Net weight kgs 1.3 kg.
Standard mounting Vertical wall.

CONFIRMING TO IP65/ NEMA-4 DEGREE PROTECTION.

INDUSTRIAL COMMUNICATIONS SIMPLIFIED .

Cables & Wireless Co.

FF 75 RAJAT ARCADE, MDC T-POINT,
AMRAWATI ROAD, WADI,
NAGPUR -440023.MAHARASHTRA ,INDIA.
PHONE:-+917104-321913, +917104-224381
FAX:- +917104-224381.

Cell: - +9198226 95746, +919145610269, +919822941190.

Website:- www.cnwcom.in.E-mail: - cnwcom@gmail.com

“(Specifications and description subjected to change without prior notice)”